



PANEL CUT-OUT

DIMENSIONS IN MILLIMETERS  
3rd ANGLE PROJECTION  
SCALE: N.T.S.

SPECIFICATION:

1. INSULATION RESISTANCE: OVER 100M Ω 500V DC.
2. DIELECTRIC STRENGTH: 200V AC ONE MINUTE.
3. BODY MATERIAL: BLACK THERMOPLASTIC W GLASS FIBER TO UL94V2-0.

DRAWN: PYQ  
MATERIAL: BLACK THERMOPLASTIC W GLASS-FIBER

CHECKED: PCS  
FINISH: AS MOULDED

TOLERANCES  
NO DECIMAL PLACE ± 0.5  
1 DECIMAL PLACE ± 0.2  
2 DECIMAL PLACES ± 0.1  
DIAMETER HOLES ± 0.1  
ANGLES ± 1/2 DEGREE  
(UNLESS OTHERWISE STATED)



TITLE: AC INLET SOCKET MS-1A/V

DRWG NO: AC-1001

ISSUE	AMEND	DATE
1	1st DRAWN	15/12/15

DRAWN	MATERIAL
PYQ	BLACK THERMOPLASTIC W GLASS-FIBER

CHECKED	FINISH
PCS	AS MOULDED



TITLE
AC INLET SOCKET MS-1A/V

DRWG NO
AC-1001