



**FRONT MOUNTING**

**REAR MOUNTING**

Rating: AC 15A 250V	Safety Regulation
Mark	UL
cUL	CUL
Rating: AC 10A 250V	Safety Regulation
Mark	YDE
	CCC
	ENEC

**SPECIFICATION:**  
 1. INSULATION RESISTANCE: OVER 100MΩ 500V DC.  
 2. DIELECTRIC STRENGTH: 2000V AC ONE MINUTE.  
 3. Body Material: Black Glass-Fiber Thermoplastic . UL 94V-2~0

**DIMENSIONS IN MILLIMETERS**  
 3rd ANGLE PROJECTION  
 SCALE: N.T.S

**DRAWN** PYQ  
**MATERIAL:** GLASS FIBRE/COMPOSITE

**CHECKED** PCS  
**FINISH:** AS MOULDED / NI PLATED

**TOLERANCES**  
 NO DECIMAL PLACE ± 0.5  
 1 DECIMAL PLACE ± 0.2  
 2 DECIMAL PLACES ± 0.1  
 DIAMETER HOLES ± 0.1  
 ANGLES ± 1/2 DEGREE  
 (UNLESS OTHERWISE STATED)



**CHK**  
 TITLE: IEC POWER INPUT RECEPTACLE W/ FUSE, PANEL MOUNT W/ REAR SOLDER TAG CONNECTION, 15A/250VAC  
 DRWG NO: AC-1011

ISSUE	AMEND	DATE
1	1st DRAWN	15/01/16

1 2 3 4 5 6 7 8 9