



P.C.B. LAYOUT

Specifications:
 Rating: DC50V 1A
 Force: 5-35N
 Contact resistance:
 Less than 30mΩ
 Insulation resistance:
 Over 100MΩ on DC 500V measured.
 Voltage withstand:
 AC 500V For 1minute,

LTR	PART NAME	QTY	MATERIAL	FINISH	REMARK
1	HOUSING	1	ABS	94HB	
2	COVER	1	ABS	94HB	
3	IRONAND STEEL	1	SHEET	0.5 MB: Cu, Sn	No.1
4	EARTH SPPING	1	BRONZE	Y=0.2 MB: Cu, Ag	
5	TIP SPPING	1	BRONZE	Y=0.4 MB: Cu, Ag	No.2
6	T TERMINAL-R	1	BRONZE	Y=0.4 MB: Cu, Ag	No.3
7	SLEEVE	1	BRASS	MB: Ni	
8	HEX NUT	1	BRASS	MB: Ni	
9	FLAT WASHER	1	STEEL	T=0.5 MB: Ni	

HEX NUT

FLAT WASHER

DIMENSIONS IN MILLIMETERS
 3rd ANGLE PROJECTION
 SCALE: N.T.S.

ISSUE	AMEND	DATE
1	1st DRAWN	02/04/18

DRAWN	MATERIAL:
PCJ	SEE TABLE

CHECKED	FINISH:
PCS	AS MOULDED

TOLERANCES
 NO DECIMAL PLACE ± 0.5
 1 DECIMAL PLACE ± 0.3
 2 DECIMAL PLACES ± 0.1
 DIAMETER HOLES ± 0.1
 ANGLES ± 1/2 DEGREE
 (UNLESS OTHERWISE STATED)



CHK

TITLE: 6.35mm PHONE JACK
 DRWG NO: PS-6130