



1. Rating : AC 125V 4A 250V 2A
2. Contact R. : 50mΩ Max.
3. Insulation R. : DC 500V 100MΩ Min.
4. Dielectric Strength : AC 1500V 1 minute.
5. Electrical Life : 20,000 make-and-break cycles at full load.
6. Operating temperature : -20°C ~ 65°C

**PC MOUNTING**

Model No	Type	Terminal Quantity	Terminal Specification	Circuitry Trait	
SW-1007	DPDT	6P	PC Terminal	(ON)	ON
				1-2	2-3
				4-5	5-6

**DIMENSIONS IN MILLIMETERS**  
3rd ANGLE PROJECTION

SCALE: N.T.S

**TOLERANCES**

- NO DECIMAL PLACE ± 0.5
- 1 DECIMAL PLACE ± 0.2
- 2 DECIMAL PLACES ± 0.1
- DIAMETER HOLES ± 0.1
- ANGLES ± 1/2 DEGREE
- (UNLESS OTHERWISE STATED)



TITLE: P/B SWITCH 4066 DPDT  
MOMENTARY PC EPOXY

DRWG NO: SW-1007

ISSUE	AMEND	DATE	DRAWN	CHECKED	FINISH:
2		22/06/18	Gen. Update	PCS	AS MOULDED
1	1st DRAWN	18/07/15			
	AMEND				

MATERIAL: COMPOSITE  
PCJ