



1. Rating : AC 125V 4A 250V 2A
2. Contact R. : 50mΩ Max.
3. Insulation R. : DC 500V 100MΩ Min.
4. Dielectric Strength : AC 1500V 1 minute.
5. Electrical Life : 50,000 make-and-break cycles at full load.
6. Operating temperature : -20°C ~ 65°C

Model No	Type	Terminal Quantity	Terminal Specification	Circuitry Trait	
SW-1009	DPDT	6P	PC Terminal	ON	ON
				1-2	2-3
				4-5	5-6

DIMENSIONS IN MILLIMETERS  
3rd ANGLE PROJECTION  
SCALE: N.T.S

DRAWN: PCJ  
MATERIAL: COMPOSITE

NO DECIMAL PLACE ± 0.5  
1 DECIMAL PLACE ± 0.2  
2 DECIMAL PLACES ± 0.1  
DIAMETER HOLES ± 0.1  
ANGLES ± 1/2 DEGREE  
(UNLESS OTHERWISE STATED)

TITLE: P/B SWITCH 4066 DPDT  
ON/OFF PC EPOXY



DRWG NO: SW-1009

ISSUE	AMEND	DATE	CHECKED	FINISH:
1	1st DRAWN	18/07/15	PCS	AS MOULDED
2	Gen. Update	22/06/18		